

FKS400V32TOP_400V

panel saw

- Solid design
- with large aluminium sliding table and extension arm ideal for processing large workpieces and cutting large, heavy panels to size
- cast iron work table (1100 x 700 mm) incl. table wideing (900 x 830 mm) and table extension (610 x 600 mm) of solid steel construction
- outrigger table 1200 x 550 mm + cross cut fence with 1950 - 3300 mm
- including scorer with own motor
- manually tiltable saw blade 0°-45° (via angle indicator)
- electric height adjustment of the main saw blade and scorer
- max. cutting height 130 mm with saw blade diameter of 400 mm

Included in delivery: main saw blade (TCT: Ø300 x 30 x 3,2 mm T(72)) and scoring saw blade (Ø120 x 20 x 3-3,8 T=2*12ES)



**YOUR
JOB.
OUR
TOOLS.**

FKS400V32TOP_400V

panel saw



technical details

motor power s1 in W	5500 (/750)
table height in mm	890
total dimensions in mm	4730 x 4860 x 1470
outrigger table in mm	1200 x 550
sawblade in mm	250-400 (/ 30)
scoring sawblade in mm	Ø120 x 20 x3,2-4,2/2,2
scoring unit speed in min-1	8000
sound power level in dB(A)	90
gross weight in kg	1.110
packaging width in mm	1.350
packaging height in mm	1.170

voltage	400 V / 50 Hz
dust collector port in mm	1x Ø100, 1x Ø80
sliding table in mm	3200 x 435
max. cutting width at parallel fence in mm	1300
sawblade speed in min-1	(I): 3000 (II): 4000 (III): 5000
scoring unit motor power in W	750
sawblade swivel	0-45°
sound pressure level in dB(A)	88,2
net weight in kg	930
packaging length in mm	2.200
EAN code	9120058379437

**YOUR
JOB.
OUR
TOOLS.**